



SMV Touch Panel L86EE/ L75EE/ L65EE/ L55EE













20pt touch Dual System 4K HDMI

HDMI Note Writing Software

Wireless Projection

Safety Lock

Product Feature

- Front USB port
- Front Physical Key
- Bottom Loudspeaker
- 4K Ultra HK Display

- IR (Infrared Ray) Touch Technology
- AG Tempered Glass 4mm Mohs level 7
- Compatible with detachable PC module

Follow us on









Products Specification



Models	L86EE	L75EE	L65EE	L55EE		
Display						
Size	86 inch	75 inch	65 inch	55 inch		
Response Time	8ms					
Aspect Ratio	16:9					
Display Area	1,895.04(H) × 1,065.96(V)mm	1,649.664(H) > 927.936(V)mn		1,209.6(H) × 680.4(V)mm		
Resolution	3,840(H) × 2,160(V)					
Pixel Pitch	0.4935 × 0.4935mm	0.4296 × 0.4296mm	0.372 × 0.372mm	0.315 × 0.315mm		
Refreshing Frequency	60Hz					
Display Color	1.07B (10bit)					
Contrast Ratio	1,200:1	1,100:1	1,200:1	1,200:1		
Viewing Angle	178°					
Back Light Unit	DLED					
Brightness with glass (typ)	350cd/m2 300cd/m2					
Brightness with glass (min)	300cd/m2					
Life Time	30,000 Hours					
Video/Audio						
Sound Channel		2	2.0			
Output Power	2 x 12W					
Display Connectors						
HDMI IN		3	3			
HDMI OUT	1					
USB 2.0	3 (Including 2 USB ports in front)					
USB 3.0	3					
TOUCH OUT	2					
VGA IN	1					
AUDIO IN		1				
AUDIO OUT		1				
SPDIF	1					
LAN (RJ45)		1				
RS232		1				

Product Specification



Models	L86EE	L75EE	L65EE	L55EE		
Touch System						
Sensing Type		Infrared Recognition				
System	Windows 10/ Windows 8/ Windows 7/ Windows XP/ Linux/ Mac/ Android/ Chrome					
Touch Point	20 points touch					
Touch Tool	Finger, Passive infrared pen					
Minimum Object Size	3mm					
Response Time	≤10ms					
Accuracy	1.5mm	±1.5mm	<1.5mm	±1.5mm		
Writing Height	≤3mm	<3mm	<3mm	3mm		
Writing Double Colors with Double Simultaneously	Support					
Touch Drive	Free Drive					
Surface Hardness	Toughened Glass with Level 7 of Mohs Standard					
Interpolation Resolution		32,768 (W) × 3	32,768 (D)			
Android System						
System Version	Android 8.0					
CPU	Dual core A73+Dual core A53					
GPU	Quad core Mali G51					
RAM	3GB					
ROM	16GB					
Power						
Power Requirements	100-240V~ 50/60Hz 5.5A	100-240V~ 50/60Hz	100-240V~ 50/60Hz 3.5A	100-240V~ 50/60Hz 3.0A		
Overall Power	550W	350W	350W	300W		
Standby Power		≤0.5W				
Physical Specification						
Key Location & Number	Front physical key, 1					
Dimension $L \times H \times D$	1,957.2 × 1,160 × 86mm	1,710 × 1,020 × 86mm	1,489× 897 × 86mm	1,269 × 773 × 86mm		
Dimension (Package) L × W × H	2,211 × 280 × 1,370mm	1,860 × 280 × 1,170mm	1,656 × 204 × 1,050mm	1,428 × 220 × 878mm		
Thickness of Machine and Wall Mount	126mm (WIB9060F)	132mm (WIB9060F)	116mm (WIB9060G)	116mm (WIB9060G)		

Products Specification



Models	L86EE	L75EE		L65EE	L55EE	
Physical Specification						
Wall-Hanging Screw Spec	M8 × 25mm					
VESA	800 × 600mm	800 × 40	00mm	600 × 400mm	400 × 200mm	
Net Weight	64.65kg	51.75kg		40.20kg	26.75kg	
Gross Weight	95.55kg	70.35kg		51.30kg	34.35kg	
Environmental Conditions	5					
Operations Temperature	0°C- 40°C					
Operation Humidity	10%			- 90%RH		
Storage Temperature	-20°C - 60°C					
Storage Humidity			10% - 90%RH			
Altitude		Below 5,000 meter				
Accessories						
Power Cord (European/ American/ British Standard Optional)			× 1 (3 m	neters)		
USB Touch Cable (Type A-B)	× 1 (5 meters)					
HDMI Cable			× 1 (3 meters)			
Writing Pen	× 2 (SW08)					
Remote Control		× 1				
Battery	× 2 (AAA)					
Random File						
Quick Start Guide			× 1			
Compatible with PC module (Optional)						
Model	MT21/ MT43A	MT21		MT21& MT43A	MT21& MT43A MT43V	

Statement


The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information. No special notice will be given if necessary.


Products Dimension



Model: L86EE



Model: L75EE



Statement


The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information. No special notice will be given if necessary.


Products Dimension



Model: L65EE



Model: L55EE



Statement

The product pictures of this specification only indicate that there may be slight difference in product effects (included but not limited to appearance, color and size). Please refer to the product. Due to the influence of product configuration and manufacturing process, the actual size/weight of the fuselage may differ.

In order to provide accurate specification parameters and product characteristics as much as possible, it is possible to adjust and revise the text description and picture effect of this specification in real time, so as to match the actual product performance, specifications and other information. No special notice will be given if necessary.